



Model PF

Application: Low cost industrial bench scale, check weighers, process weighing, bag filling.

Dimensions: 174 x 65 x 60 mm
Hole CD 19 x 30 mm



Technical Data

Capacities	100, 150, 200, 250, 300, 500, 750, 1000 kg
Sensitivity	2.0 ± 10% mV/V
Non-Linearity	± 0.02% FS
Hysteresis	± 0.02% FS
Repeatability	± 0.02% FS
Creep (20 min)	± 0.02% FS
Temp. effect span	± 0.015% FS/10°C
Temp effect zero	± 0.02% FS/10°C
Temperature compensated range	-10 ~ +50°C
Input resistance	400 ± 16Ω
Output resistance	350 ± 3Ω
Insulation resistance	> 5000 MΩ (@ 50V DC)
Safe load	150% FS
Ultimate load	200% FS
Recommended excitation	10V (DC/AC)
Maximum excitation	12V (DC/AC)
Construction	Aluminium Alloy
Environmental protection	IP 65
Max. platform size	600 X 600 mm

Haris Sensor Technologies Private Limited

Row House No.11, Narayani C.H.S. Ltd., Sector 2, Airoli, Navi Mumbai - 400 708.
TeleFax: +91-22-2779 6901 ~ 06 ☎ E-mail: harisent@vsnl.net ☎ Website: harissensor.com

HARIS